

CLAIMS

1. A warning sign comprising first and second parts pivotably interconnected at their in use upper ends and pivotable between a first storage position in which the first and second parts are arranged in side-by-side relationship and a second operative position in which the first and second parts are at an angle to one another, detent means for releasably retaining the first and second parts in the second operative position, and a third part releasably supportable by the detent means.
2. A warning sign as claimed in claim 1, wherein the two parts have ground contacting foot portions at their in use lower ends, so that, with said foot portion or portions of one part spaced from said foot portion or portions of the other part, the sign will be self-supporting on the ground.
3. A warning sign as claimed in claim 1 or claim 2, wherein the detent means comprises at least one projection and at least one corresponding aperture or recess, the projection being arranged to fit in the aperture or recess as a snap or friction fit when the first and second parts are in the second operative position.
4. A warning sign as claimed in claim 3, wherein the first and second parts each have one said projection which cooperates with one said corresponding aperture or recess formed in the other part.
5. A warning sign as claimed in claim 3 or claim 4, wherein the third part includes a

support portion having one or more openings dimensioned to receive a corresponding said projection therethrough.

6. A warning sign as claimed in claim 5, wherein the or each opening in the third  
5 part is a through-hole.

7. A warning sign as claimed in claim 5 or claim 6, wherein the said projection can  
only be inserted into the corresponding opening of the third part when the first and  
second parts are in the first storage position.  
10

8. A warning sign as claimed in any one of claims 5 to 7, wherein the said  
projection can only be removed from the corresponding opening of the third part when  
the detent means is released.

15 9. A warning sign as claimed in claim 5, wherein the or each opening in the third  
part is a recess formed in an edge of the third part.

10. A warning sign as claimed in claim 9, wherein at least one said recess is keyhole  
shaped so as to be snap-fit engageable with the said projection of the detent means.

20

11. A warning sign as claimed in claim 9 or claim 10, wherein the third part, in use,  
is engageable with and disengageable from the projection of the detent means, when the  
first and second parts are in the first storage position and the second operative position.

12. A warning sign as claimed in any one of the preceding claims, further comprising a fourth display part releasably engageable with the third part.

13. A warning sign as claimed in claim 12, wherein the third part includes an elongate  
5 channel in which the bottom end of the fourth display part is receivable.

14. A warning sign as claimed in claim 12, wherein the third part comprises two members, each member including an elongate channel in which a side of the fourth display part is, at least in part, receivable.

10

15. A warning sign as claimed in claim 12, wherein the third part includes a transparent holder for holding the fourth display part.

16. A warning sign as claimed in claim 15, wherein the transparent holder is a sleeve  
15 into which the fourth display part can be slidably inserted.

17. A warning sign substantially as hereinbefore described with reference to the Figures 1 to 3, Figure 4, Figure 5, or Figure 6 of the accompanying drawings.